#TECHNIC, INC. SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product Name: GOLD POWDER 407 Product Code: 12-407 Recommended use: Conductive filler; for industrial use only. Supplier: Technic Inc. 1 Spectacle Street Cranston, RI 02910 USA Telephone no: 401-781-6100 Emergency no: ChemTrec 800-424-9300, Outside the USA and Canada 703-527-3887

SECTION 2. HAZARD IDENTIFICATION

Classification:

Flammable Liquids, Category 2 Eye Damage/Irritation, Category 2A Specific Target Organ Toxicity (Single Exposure), Category 3

Label elements and precautionary statements:

Signal word: Danger



Hazards not otherwise classified: None

Hazard statement(s):

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness

Precautionary statement(s):

Keep away from heat, sparks, open flames and hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical, ventilating and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves, clothing and eye and face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
In case of fire: Use water to extinguish.
Store in a well-ventilated place. Keep cool.
Wash hands thoroughly after handling.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Avoid breathing dust, fume, gas, mist, vapors or spray.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Dispose of contents and container in accordance with local, state and federal regulations.

SECTION 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name Gold (metallic) Isopropanol

CAS Number 7440-57-5 67-63-0 **EINECS Number** 231-165-9 200-661-7

Concentration 90% 10%

SECTION 4. FIRST AID MEASURES

Inhalation:

Remove patient to fresh air. Support breathing if required. Obtain medical treatment for dizziness, unconsciousness or irritation or difficulty in breathing.

Skin contact:

Remove contaminated clothing and wash affected area thoroughly with soap and water. Launder clothing before rewearing. Seek medical attention for prolonged skin irritation.

Eye contact:

Flush with water, including under lids, for fifteen minutes. Obtain immediate medical attention.

Ingestion:

If patient is conscious, rinse mouth and drink at least two large glasses of water. DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain immediate medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use media appropriate for surrounding fire such as foam, extinguishing powder, carbon dioxide or water spray. In case of fire, cool endangered containers with water spray.

Unsuitable extinguishing media: High pressure water jet.

Specific hazards in case of fire: May emit toxic fumes under fire conditions.

Special protective equipment and precaution for fire fighters: For fires in enclosed areas, wear self-contained breathing apparatus and full protective gear. Do not inhale combustion gases.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear appropriate skin, eye and respiratory protection. Do not eat, drink or smoke while cleaning up. Ensure adequate ventilation.

Methods and materials for containment and cleaning up:

Extinguish all sources of ignition and wear protective gear including respiratory protection. Confine spill. If spill is large, pump as much liquid as possible into suitable containers for disposal. Absorb small spills and spill residues with non-flammable material (sand, clays, etc.) Shovel into containers and treat as solid waste. Incinerate in accordance with local, state and federal regulations. Do not allow this material to enter storm or sanitary sewers or other waterways. (see also Section 13).

Environmental precautions:

Prevent spills and rinsings from entering storm or sanitary sewers or other waterways and contact with soil.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid contact with eyes. Avoid prolonged repeated skin contact and breathing mists or vapors. Use in well-ventilated area. Do not empty waste into sanitary drains.

Conditions for safe storage, including incompatibilities:

Store in a cool, dry area. Use with adequate ventilation. Keep container tightly closed when not in use. Store only in the original container.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits:

Isopropanol

ACGIH TLV 200 ppm TWA 400 ppm STEL OSHA PEL 400 ppm Other Limits 400 ppm NIOSH REL

Appropriate engineering controls:

Use in well-ventilated area with local exhaust.

Respiratory protection:

Wear appropriate, approved respiratory protection when ventilation is inadequate to meet exposure limits.

Eye protection:

Chemical splash goggles or safety glasses with side shields must be worn.

Skin protection:

Wear rubber or neoprene gloves. Wear rubber apron and long sleeves to prevent skin contact. Wash hands thoroughly with soap and water after handling and before eating or smoking.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Metal powder in solvent Color: Gold metal powder; clear, colorless solvent Odor: Alcoholic Odor threshold: Not available **pH:** Not applicable Melting/freezing point: Not determined Initial boiling point: 82 °C (180 °F) solvent Flash point: 12 °C (53 °F) solvent **Evaporation rate:** Not available Flammability (solid, gas): Not applicable Upper/lower explosion limits: 12.7%/2.0% solvent Vapor pressure: Not determined Vapor density: 2.1 Relative density (H₂O = 1) @25 °C: 0.79 solvent Solubility: Completely soluble in water at 20 °C solvent Partition coefficient octanol/water: Not determined Auto-ignition temperature: 399 °C (750 °F) solvent **Decomposition temperature:** Not available **Viscosity:** Not determined

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Stable, non-reactive when stored and used according to recommendations.
 Chemical stability: No decomposition if used according to specifications.
 Possibility of hazardous reactions: Vapor may form explosive mixture with air.
 Conditions to avoid: Heat, flames, sparks, high temperatures and direct sunlight.
 Incompatible materials: Concentrated acids and oxidizing agents.
 Hazardous decomposition products: Carbon monoxide and carbon dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Routes of Exposure and Symptoms

Inhalation:	Vapor or mist may cause irritation to nose and throat.
Ingestion:	May cause abdominal discomfort, nausea, vomiting and diarrhea.
Skin Contact:	Brief contact is usually not irritating. Prolonged contact may cause irritation and redness.
Eye Contact:	Causes serious eye injury with possible corneal burns.

Acute and Chronic Effects from Short- and Long-term Exposure:

See Routes of Exposure and Symptoms above.

Acute Oral Toxicity:	LD50: 5045 mg/kg (rat, isopropanol)			
Acute Dermal Toxicity:	LD50: 12,800 mg/kg (rabbit, isopropanol)			
Acute Inhalation Toxicity:	LCLo: 12,800 ppm, 3 hours (mouse, isopropanol)			
Acute Eye Irritation:	10 mg, moderate (rabbit, isopropanol)			
Dermal Irritation:	500 mg, mild (rabbit, isopropanol)			

Carcinogen Listings:

IARC: No NTP: No OSHA: No

Reproductive Effects: No applicable information available.

Target Organ Effects: No applicable information available.

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity: LC50: 9640 mg/l, 96 hours (Fathead minnow, isopropanol) EC50: 5102 mg/l, 24 hours (Daphnia magna, isopropanol)

Persistence and degradability: There are no data reported for this material.

Bio-accumulative potential: There are no data reported for this material.

Mobility in soil: Accidental spillage may lead to penetration in the soil and groundwater. Improper handling and disposal of this material may cause environmental damage.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal:

Disposal of this material is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

SECTION 14. TRANSPORT INFORMATION

Classification for shipment by road or rail, sea (IMDG) and air (IATA/ICAO):

UN proper shipping name:	Flammable Liquids, N.O.S. (Isopropanol, Metallic Mixture)
UN number:	UN1993
Transport hazard class:	3
Packing group:	II

Marine Pollutant: No

SECTION 15. REGULATORY INFORMATION

Inventory Status:

All components are on TSCA, EINECS/ELINCS, AICS, and DSL. **U.S. Regulations:**

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III:

SARA (311/312) HAZARD CATEGORIES:

None	<u>X</u>	_Immediate	Delayed	_X	Fire	Reactive	Pressure	generating
------	----------	------------	---------	----	------	----------	----------	------------

SARA 313: This product contains the following SARA 313 Toxic Release Chemicals.Chemical NameCAS NumberNone

The following product components are cited on the lists below:Chemical NameCAS NumberNoneList CitationsCalifornia Proposition 65 List

SECTION 16. OTHER INFORMATION

VOC (Volatile Organic Compounds): Isopropanol, 10%

HMIS Ratings:

Health: 2 Flammability: 3 Reactivity: 0 Personal Protection: C

Prepared by: Allan H. Reed

SDS Preparation date: October 19, 2015 Supersedes previous version: New SDS

This SDS contains revisions in the following section(s): Not applicable. New SDS

The information contained herein is accurate to the best of our knowledge. Technic Inc. makes no warranty of any kind, express or implied, concerning the safe use of this material in any process or in combination with other substances.

End of Safety Data Sheet